


8G27

SPECIFICATIONS

| | |
|-------------------------------------|--------------------------------|
| Nominal Voltage (V) | 12V |
| Capacity at C/100 | 99Ah |
| Capacity at C/20 | 88Ah |
| Weight | 63.2 lbs. (28.7 kg) |
| Plate Alloy | Lead Calcium |
| Posts | Forged Terminals & Bushings |
| Container/Cover | Polypropylene |
| Operating Temperature Range | -76°F (-60°C) - 140°F (60°C) |
| Charge Voltage @ 68°F (20°C) | |
| Cycle | 2.30 - 2.35VPC |
| Float | 2.25 - 2.30VPC |
| Vent | Self-sealing (2 PSI operation) |
| Electrolyte | Sulfuric acid thixotropic gel |
| Terminal | U (SAE/STUD) |



Rated non-spillable by ICAO, IATA and DOT

Made in the U.S.A. by East Penn Manufacturing Co, Inc.

Distributed by:


Valve-Regulated, Gelled-Electrolyte Battery



DIMENSIONS

| | |
|--------------------|----------------|
| Length (mm) | 12.83 (326 mm) |
| Width (mm) | 6.80 (173 mm) |
| Height (mm) | 9.88 (251 mm) |

**Gel Cycle Life vs Depth of Discharge at +25°C (77°F)
Based on BCI 2-hour Capacity**



MK Battery

1631 South Sinclair Street • Anaheim, California 92806

Toll Free: 800-372-9253 • Fax: 714-937-0818 • E-mail: sales@mkbattery.com

