



LIVEN LV Series

AGM (Absorbent Glass Material) technology with gas recombination. VRLA (Valve Regulated Lead Acid Battery). Maintenance-Free Sealed Lead Acid Battery. Battery with 5 years design life in float service. Cycle use 1: Up to 260 cycles at 100% DOD. Cycle use 2: Up to 500 cycles at 50% DOD.

Application:

- Telecommunications
- Alarm and security system
- Uninterrupted Power Supplies
- Communication power supply
- Medical equipments
- DC power supply
- Emergency backup power supply

Dimensions:


Length	125±1.5mm (5.28 inches)
Width	33±1.5mm (1.34 inches)
Height	60±1.5mm (2.36 inches)
Total Height	64±1.5mm (2.60 inches)

Specification:

Cells Per Unit	3
Voltage Per Unit	6
Nominal Capacity	3.2Ah@20hour-rate to 1.75V per cell @25°C
Weight	Approx. 0.65 Kg ±2%
Internal Resistance	Approx. 25 mΩ
Terminal	F1
Max. Discharge Current	32A (5 sec)
Short Circuit Current	166A
Design Life	5 years (Float charging) Eurobat (20°C): 3-5 years
Recommended Maximum Charging Current	0.96 A
Standby Use Voltage	6.85 V~6.95 V @ 25°C Temperature Compensation: -3mV/°C/Cell
Cycle Use Voltage	7.30 V~7.40 V @ 25°C Temperature Compensation: -4mV/°C/Cell
Operating Temperature Range	Discharge: -15°C~50°C Charge: -10°C~45°C Storage: -15°C~50°C
Normal Operating Temperature Range	25°C±5°C
Self Discharge	LIVEN Valve Regulated Lead Acid (VRLA) batteries can be stored for up to 6 months at 25°C and then recharging is recommended. Monthly Self-discharge ratio is less than 3% at 25°C. Please charge batteries before using.
Container Material	A.B.S. UL94-HB, UL94-V0 Optional.



Drawing:




Constant Current Discharge (CC, Unit: A) at 25°C (77°F)

F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	12.69	8.274	6.104	3.533	2.041	1.204	0.875	0.697	0.589	0.393	0.320	0.167
1.65V	12.23	8.028	5.944	3.455	2.003	1.187	0.864	0.688	0.582	0.389	0.317	0.165
1.70V	11.63	7.704	5.734	3.352	1.953	1.163	0.848	0.677	0.573	0.384	0.313	0.164
1.75V	10.87	7.286	5.460	3.218	1.887	1.132	0.828	0.662	0.561	0.377	0.308	0.161
1.80V	9.901	6.751	5.108	3.044	1.801	1.091	0.801	0.641	0.545	0.368	0.301	0.158
1.85V	8.713	6.082	4.663	2.822	1.691	1.038	0.765	0.615	0.524	0.355	0.291	0.154


Constant Power Discharge (CP, Unit: W/Battery) at 25°C (77°F)

F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	65.52	42.84	32.49	19.53	11.61	6.96	5.10	4.08	3.45	2.34	1.92	0.99
1.65V	64.83	42.66	32.31	19.38	11.52	6.90	5.04	4.05	3.42	2.31	1.89	0.99
1.70V	62.34	41.40	31.44	18.93	11.28	6.78	4.98	3.99	3.39	2.28	1.89	0.99
1.75V	59.28	39.84	30.36	18.36	10.95	6.63	4.89	3.90	3.33	2.25	1.86	0.96
1.80V	54.96	37.56	28.83	17.55	10.50	6.42	4.74	3.81	3.24	2.22	1.80	0.96
1.85V	49.23	34.44	26.67	16.41	9.93	6.15	4.56	3.66	3.12	2.13	1.74	0.93


Discharge Characteristics Curve




Charge Characteristic Curve For Standby Use




Cycle Life In Relation To Depth Of Discharge




Relationship Between Charging Voltage And Temperature




Temperature Effects On Capacity




Storage Characteristics



Effect Of Temperature On Long Term Life



Life Characteristics Of Standby Use



(Note) All above information shall be changed without prior notice. LIVEN Battery reserves the right to explain and update the latest information.