

LP SERIES-General Purpose

LP12-1.9 (12V1.9AH)


Specification

Nominal Voltage	12V	
Nominal Capacity(20HR)	1.9AH	
Dimension	Length	178±2mm (7.00 inches)
	Width	35±1mm (1.38 inches)
	Container Height	60±1mm (2.36 inches)
	Total Height (with Terminal)	66±1mm (2.60 inches)
Approx Weight	Approx 0.87 kg (1.92lbs)	
Terminal	T1	
Container Material	ABS	
Rated Capacity	1.90 AH/0.095A	(20hr , 1.80V/cell,25°C/77°F)
	1.77 AH/0.177A	(10hr, 1.80V/cell,25°C/77°F)
	1.61 AH/0.323A	(5hr, 1.75V/cell,25°C/77°F)
	1.45 AH/0.485A	(3hr, 1.75V/cell,25°C/77°F)
	1.19 AH/1.19A	(1hr, 1.60V/cell,25°C/77°F)
Max. Discharge Current	28.5A (5s)	
Internal Resistance	Approx 80mΩ	
Operating Temp.Range	Discharge : -15~50°C (5~122°F)	
	Charge : 0~40°C (32~104°F)	
	Storage : -15~40°C (5~104°F)	
Nominal Operating Temp. Range	25±3°C (77±5°F)	
Cycle Use	Initial Charging Current less than0.57A.Voltage	
	14.4V~15.0V at 25°C(77°F)Temp. Coefficient -30mV/°C	
Standby Use	No limit on Initial Charging Current Voltage	
	13.5V~13.8V at 25°C(77°F)Temp. Coefficient -20mV/°C	
Capacity affected by Temperature	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge	Leoch LP series batteries may be stored for up to 6 months at 25°C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	



Applications

- ◆ All purpose
- ◆ Uninterruptable Power Supply (UPS)
- ◆ Electric Power System (EPS)
- ◆ Emergency backup power supply
- ◆ Emergency light
- ◆ Railway signal
- ◆ Aircraft signal
- ◆ Alarm and security system
- ◆ Electronic apparatus and equipment
- ◆ Communication power supply
- ◆ DC power supply
- ◆ Auto control system



Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	3.62	2.78	2.30	1.99	1.54	1.13	0.96	0.565	0.442	0.359	0.293	0.254	0.205	0.171	0.094
1.80V/cell	4.86	3.55	2.78	2.35	1.82	1.32	1.07	0.617	0.476	0.384	0.315	0.273	0.218	0.177	0.095
1.75V/cell	5.48	3.90	3.04	2.53	1.88	1.37	1.12	0.640	0.485	0.392	0.323	0.280	0.221	0.181	0.096
1.70V/cell	6.03	4.25	3.24	2.66	1.96	1.42	1.16	0.656	0.498	0.403	0.331	0.286	0.224	0.185	0.098
1.65V/cell	6.65	4.59	3.45	2.83	2.07	1.46	1.18	0.665	0.519	0.417	0.340	0.292	0.228	0.189	0.099
1.60V/cell	7.33	4.98	3.69	3.01	2.19	1.52	1.19	0.694	0.535	0.430	0.352	0.299	0.230	0.191	0.100


Constant Power Discharge (Watts) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	6.62	5.13	4.29	3.75	2.93	2.18	1.84	1.10	0.862	0.703	0.575	0.500	0.405	0.339	0.186
1.80V/cell	8.79	6.48	5.12	4.37	3.41	2.51	2.05	1.19	0.922	0.746	0.614	0.534	0.428	0.349	0.188
1.75V/cell	9.69	7.01	5.52	4.66	3.51	2.58	2.14	1.23	0.935	0.760	0.628	0.547	0.435	0.358	0.190
1.70V/cell	10.38	7.46	5.81	4.86	3.63	2.68	2.20	1.26	0.960	0.779	0.643	0.558	0.440	0.365	0.193
1.65V/cell	11.28	7.98	6.14	5.12	3.80	2.72	2.23	1.27	0.996	0.803	0.658	0.568	0.446	0.372	0.195
1.60V/cell	12.16	8.47	6.45	5.39	3.98	2.82	2.24	1.32	1.022	0.826	0.678	0.579	0.450	0.375	0.196


Dimensions

T1 Terminal


Unit: mm [inches]




Discharge Characteristics




Float Charging Characteristics




Temperature Effects in Relation to Battery Capacity




Effect of Temperature on Long Term Float Life



Cycle Life in Relation to Depth of Discharge



Self Discharge Characteristics



Sales Office

China sales office:

Add: 5th Floor, Xinbaohui Bldg., Nanshan, Shenzhen, China. 518052
 Tel: +86-755-86036060 (100 lines)
 Fax: +86-755-26067269
 E-mail: export@leoch.com
 Http://www.leoch.com

North America sales office:

Add: 19751 Descartes, Unit A, Foothill Ranch, CA 92610, USA
 Tel: 949-588-5853
 Fax: 949-588-5966
 E-mail: sales@leoch.us
 Http://www.leoch.us

Europe sales office:

Add: 9B Wheatstone Park, Waterwells Business Park, Gloucester, GL2 2AQ. UK.
 Tel: +44(0) 1452 729428
 Fax: +44 (0)1452-690125
 E-mail: Sales.Europe@leoch.com