

LIVEN LV Series

AGM (Absorbent Glass Material) technology with gas recombination. VRLA (Valve Regulated Lead Acid Battery). Maintenance-Free Sealed Lead Acid Battery. Battery with 5 years design life in float service.

Cycle use 1: Up to 260 cycles at 100% DOD.

Cycle use 2: Up to 500 cycles at 50% DOD.

Application:


- Telecommunications
- Uninterrupted Power Supplies
- Medical equipments
- Emergency backup power supply
- Alarm and security system
- Communication power supply
- DC power supply

Dimensions:

Length	151±1.5mm (5.94in)
Width	65±1.5mm (2.56in)
Height	94±1.5mm (3.70in)
Total Height	100±1.5mm (3.94in)


Specification:

Cells Per Unit	6
Voltage Per Unit	12V
Nominal Capacity	9.0Ah @20hour-rate to 1.75V per cell @25°C
Weight	Approx. 2.55Kg ±2% (5.62lbs)
Internal Resistance	Approx. 18mΩ
Terminal	F2
Max. Discharge Current	90A (5sec)
Short Circuit Current	450A
Design Life	5 years (Float charging) Eurobat (20°C): 3-5 years
Recommended Maximum Charging Current	2.7A
Standby Use Voltage	13.7V~13.9V @ 25°C Temperature Compensation: -3mV/°C/Cell
Cycle Use Voltage	14.6V~14.8V @ 25°C Temperature Compensation: -4mV/°C/Cell
Operating Temperature Range	Discharge: -15°C~50°C Charge: -10°C~45°C Storage: -15°C~50°C
Normal Operating Temperature Range	25°C±5°C
Self Discharge	LIVEN Valve Regulated Lead Acid (VRLA) batteries can be stored for up to 6 months at 25°C and then recharging is recommended. Monthly Self-discharge ratio is less than 3% at 25°C. Please charge batteries before using.
Container Material	A.B.S. UL94-HB, UL94-V0 Optional.


Technical Drawing:

Constant Current Discharge (CC, Unit: A) at 25°C (77°F)

F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	35.68	23.27	17.17	9.936	5.741	3.387	2.462	1.961	1.655	1.106	0.901	0.469
1.65V	34.39	22.58	16.72	9.717	5.634	3.338	2.430	1.936	1.636	1.095	0.892	0.465
1.70V	32.72	21.67	16.13	9.429	5.494	3.272	2.386	1.904	1.611	1.080	0.881	0.460
1.75V	30.56	20.49	15.36	9.051	5.308	3.184	2.328	1.861	1.577	1.060	0.866	0.453
1.80V	27.85	18.99	14.37	8.562	5.067	3.070	2.252	1.804	1.532	1.034	0.846	0.444
1.85V	24.50	17.11	13.12	7.937	4.755	2.921	2.153	1.730	1.473	0.999	0.819	0.433


Constant Power Discharge (CP, Unit: W/Battery) at 25°C (77°F)

F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	368.52	240.90	182.76	109.92	65.40	39.12	28.62	22.92	19.44	13.14	10.80	5.64
1.65V	364.62	239.94	181.74	109.08	64.86	38.82	28.44	22.74	19.32	13.08	10.68	5.58
1.70V	350.70	232.86	176.82	106.44	63.42	38.16	28.02	22.44	19.02	12.90	10.56	5.52
1.75V	333.54	224.16	170.82	103.26	61.62	37.32	27.42	22.02	18.72	12.66	10.38	5.46
1.80V	309.18	211.32	162.06	98.64	59.10	36.12	26.64	21.42	18.24	12.42	10.20	5.34
1.85V	276.90	193.80	150.06	92.34	55.86	34.56	25.56	20.58	17.58	12.00	9.90	5.22


Discharge Characteristics Curve




Charge Characteristic Curve For Standby Use




Cycle Life In Relation To Depth Of Discharge




Relationship Between Charging Voltage And Temperature




Temperature Effects On Capacity



Storage Characteristics



Effect Of Temperature On Long Term Life



Life Characteristics Of Standby Use

