



LIVEN LVG Series

LVG Pure Gel series are manufacturing with high porosity PE separator and patented Gel electrolyte. The LVG series Valve Regulated Lead Acid (VRLA) is Pure Gel with 15 years floating design life. This battery its ideal for standby or frequent cyclic discharge applications under extreme environment. Suitable for Solar and Wind system, Marine, Telecom, UPS.

Deep discharge cycles 1: 450 cycles at 100% DOD.

Deep discharge cycles 2: 1300 cycles at 50% DOD.

Applications:

- Telecommunications
- UPS
- Medical equipments
- Solar System
- Wind Power System
- Auto Control System
- CATV
- Marine


Dimensions:

Length	521±1.5mm (20.5in)
Width	268±1.5mm (10.6in)
Height	220±1.5mm (8.66in)
Total Height	225±1.5mm (8.86in)

Specifications:

Cells Per Unit	6
Voltage Per Unit	12V
Nominal Capacity	260.0Ah @20hour-rate to 1.75V per cell @25°C
Weight	Approx. 71.0Kg ±2% (156.53lbs)
Internal Resistance	Approx. 4.0mΩ
Terminal	R8.1
Max. Discharge Current	2600A (5sec)
Design Life	15 years floating Eurobat (20°C): >12 years Very Long Life
Recommended Maximum Charging Current	52.0A
Standby Use Voltage	13.6V~13.8V @ 25°C Temperature Compensation: -3mV/°C/Cell
Cycle Use Voltage	14.2V~14.4V @ 25°C Temperature Compensation: -4mV/°C/Cell
Operating Temperature Range	Discharge: -40°C~60°C Charge: -20°C~50°C Storage: -40°C~60°C
Normal Operating Temperature Range	25°C±5°C
Self Discharge	LIVEN Valve Regulated Lead Acid (VRLA) batteries can be stored for up to 6 months at 25°C and then recharging is recommended. Monthly Self-discharge ratio is less than 3% at 25°C. Please charge batteries before using.
Container Material	A.B.S. UL94-HB, UL94-V0 Optional.

Technical Drawings:




Constant Current Discharge (CC, Unit: A) at 25°C (77°F)

F.V. / Time	15min	30min	1h	2h	3h	4h	5h	8h	10h	20h
1.60V	345.2	226.5	141.2	86.3	64.7	51.6	43.3	29.3	24.1	13.5
1.65V	330.0	217.5	136.3	83.5	62.7	50.2	42.2	28.9	23.8	13.3
1.70V	309.1	207.9	131.9	80.8	61.0	48.8	41.1	28.5	23.5	13.2
1.75V	287.7	198.7	127.1	77.9	59.2	47.6	40.0	28.1	23.2	13.0
1.80V	265.6	189.9	122.2	75.2	57.3	46.2	39.0	27.6	22.9	12.9
1.85V	220.4	163.5	109.6	68.9	53.0	43.0	36.4	25.9	21.5	12.2


Constant Power Discharge (CP, Unit: W/Battery) at 25°C (77°F)

F.V. / Time	15min	30min	1h	2h	3h	4h	5h	8h	10h	20h
1.60V	4114.8	2805.0	1809.0	1114.8	842.4	675.6	568.8	389.4	323.4	181.8
1.65V	3955.2	2716.2	1759.8	1084.8	821.4	660.0	556.2	385.2	319.8	179.4
1.70V	3795.0	2627.4	1710.6	1054.8	801.0	644.4	543.6	381.0	315.6	177.0
1.75V	3583.2	2536.8	1657.8	1022.4	780.6	630.0	531.6	376.2	312.0	175.2
1.80V	3355.2	2449.2	1603.8	990.6	759.0	614.4	520.2	370.8	308.4	173.4
1.85V	2823.6	2130.6	1447.2	912.6	705.0	573.0	486.6	349.2	290.4	165.0


Discharge Characteristics Curve




Charge Characteristic Curve For Standby Use




Cycle Life In Relation To Depth Of Discharge




Relationship Between Charging Voltage And Temperature




Temperature Effects On Capacity



Storage Characteristics



Effect Of Temperature On Long Term Life



Relationship of OCV and State of Charge (20°C)

