



### LIVEN LVHR Series

AGM (Absorbent Glass Material) technology with gas recombination. The LVHR series Valve Regulated Lead Acid (VRLA) battery is designed for heavy load discharge applications with 10~12 years design life in float service. By using strong grids and specially designed active material is with lower I.R, lower self discharge rate, high power, and longer service life performance. Generally the LVHR series offers 30% more power output than the standard range.


### Applications:

- High Power
- UPS
- Datacenters
- Emergency backup PW
- Security system
- Communication power supply
- DC power supply

### Dimensions:

Length	306±1mm (12.1in)
Width	169±1mm (6.65in)
Height	211±1mm (8.31in)
Total Height	215±1mm (8.46in)

### Technical Drawings:



### Constant Current Discharge (CC, Unit: A) at 25°C (77°F)


F.V./ Time	10min	15min	20min	30min	45min	60min	2h	3h	4h	5h
1.60V	234.74	190.36	152.51	114.22	80.47	60.70	34.70	24.90	20.10	17.40
1.67V	224.91	184.95	146.02	110.56	77.88	59.20	34.40	24.70	19.90	17.30
1.70V	218.36	179.55	142.77	108.50	76.36	58.20	34.20	24.60	19.80	17.20
1.75V	209.63	173.06	138.44	105.87	74.52	57.10	33.70	24.40	19.70	17.10
1.80V	197.62	163.32	130.87	101.97	71.82	55.30	32.80	23.70	19.10	16.60

### Constant Power Discharge (CP, Unit: W/Battery) at 25°C (77°F)


F.V./ Time	10min	15min	20min	30min	45min	60min	2h	3h	4h	5h
1.60V	2678.1	2060.4	1731.4	1301.0	952.6	702.0	406.2	294.6	237.0	207.0
1.67V	2552.5	1980.0	1661.3	1253.8	919.5	684.0	402.6	291.6	235.2	205.2
1.70V	2486.3	1939.2	1629.5	1233.6	899.6	672.0	400.2	290.4	234.0	204.6
1.75V	2380.6	1872.5	1572.2	1206.7	879.8	660.0	394.2	288.6	232.2	203.4
1.80V	2248.3	1769.5	1489.5	1159.4	846.7	642.0	384.0	280.2	225.6	196.8

Specifications:	
Cells Per Unit	6
Voltage Per Unit	12V
Nominal Capacity	1980W @15min-rate to 10.02V per battery @25°C
Weight	Approx. 28.50Kg ±2% (62.80lbs)
Internal Resistance	Approx. 5.0mΩ
Terminal	R6.5
Max. Discharge Current	800A (5sec)
Design Life	Up to 10 years in Standby use (25°C) Eurobat (20°C): 10~12 years Long Life
Recommended Max. Charging Current	26.4A
Reference Capacity	C20 100Ah
Standby Use Voltage	13.5V~13.8V @ 25°C Temperature Compensation: -18mV/°C/Cell
Cycle Use Voltage	14.5V~15.0V @ 25°C Temperature Compensation: -30mV/°C/Cell
Operating Temperature Range	Discharge: -15°C~50°C Charge: -10°C~45°C Storage: -15°C~50°C
Normal Operating Temperature Range	25°C±5°C
Self Discharge	LIVEN Valve Regulated Lead Acid (VRLA) batteries can be stored for up to 6 months at 25°C and then recharging is recommended. Monthly Self-discharge ratio is less than 3% at 25°C. Please charge batteries before using.
Container Material	A.B.S. UL94-HB, UL94-V0 Optional.


**Discharge Characteristics Curve**




**Charging Characteristics**




**Cycle Life In Relation To Depth Of Discharge**




**Relationship Between Charging Voltage And Temperature**




**Temperature Effects On Capacity**



**Storage Characteristics**



**Effect Of Temperature On Long Term Life**



**Relationship For OCV And Capacity**

