

LITHIUM BATTERIES
 LiFePO_4

Upower
ecoline



UE SERIES
UE-FT-12Li100



12.8 V



100 Ah

RB | Reguero[®]
Baterías

UE-FT-12Li100

UE SERIES

PRODUCT DESCRIPTION

Lithium-ferrophosphate (LiFePO₄) battery designed to replace lead-acid with better performance:

- Very high energy density and capacity.
- Longer useful life.
- Greater safety (no maintenance).
- Parallelisable and can be assembled up to 4 units (4x4).

APPLICATIONS


- UPS/EPS
- TELECOM
- Accumulation of solar surplus
- Autonomous mobility

MAIN TECHNICAL SPECIFICATIONS







Rated Capacity:		100 Ah
Rated Voltage:		12,8 V
Recommended Charge Current:	(0.2 C)	20 A
Maximum Charge Current (*):		100 A
Recommended Discharge Current:	(0.2 C)	20 A
Maximum Discharge Current (*):		100 A
Life Cycles:	(100% DoD)	2500 cycles
Operating Temperature:	Charge:	0°C ~ 45°C
	Discharge:	-20°C ~ 60°C
Storage Temperature:		-10°C ~ 35°C

(*) Charging and discharging at higher than recommended currents can cause a decrease in the performance and life expectancy of the battery.

DIMENSIONS



OPERATING CURVES



UE-FT-12Li100

UE SERIES

ELECTRICAL SPECIFICATIONS

Bulk charge voltage:	14.6 V
Float charge voltage	13,8-14V
Discharge Cutoff Voltage:	10 V
Internal Resistance:	≤ 10 mΩ

OTHER SPECIFICATIONS

Dimensions (L x W x H):	395 x 110 x 286 mm
Weight:	Approx. 10 kg
Output Connector:	M8

PROTECTIONS

- Overload Protection
- Overload Protection
- Load/Discharge Overvoltage Protection
- Short Circuit Protection
- Excessive Temperature Protection

CERTIFICATIONS

UN 38.8 MSDS , DG certificate, CE